


- 2 RHEINZINK - Double Standing Seam Roof
- 16 RHEINZINK - Building Profile
 - a Eaves flashing
 - n Non continuous clip
 - q Cover flashing
 - r Render flashing
 - p Valley profile, fall 5mm/1m
- 18 Support Profile
 - a Galvanized steel
- 19 Separating Layer
 - a Structured underlay VAPOZINC®
 - c Structured mat AIR-Z
- 20 Substructure
 - d Softwood boarding, non continuous
 - f OSB/ veneer plywood sheathing, thickness min. 22 mm,
- 21 Batten/ Squared Timber
 - Squared Timber
- 22 Functional Layer
 - c Waterproof sheeting
- 23 Supporting Structure
- 25 Thermal Insulation
 - c Linitherm thermal insulation panel with 22 mm OSB outer face, insitu foam to any cavities
- 27 Vapour Control Layer
 - b sd value >100m



STANDARD DETAIL

Parapet Gutter, Linitherm + Structured underlay -	Title	Scale
		1:2
		Size
		A3
	Detail-Nr.	Drawn
	09020203021211000203_GB_en	gam
		Date
		11.03.14

The detail describes an optional design in standard cases based on a European climate. Any user of this document is responsible to verify the feasibility of the solution with respect to the specific local situation and conditions. Using the documents provided by RHEINZINK is a service, which excludes liability for damages or claims of any kind. Contingent liability for malice or gross negligence is unaffected.